

F8n Pro Operation Confirmed External Power Supply

As of April 2022, the operation confirmed external power supplies are as follows.

BRANDS	MODEL	RECOMMENDED SETTING
Anton Bauer	Digital G90 Battery	Shutdown Voltage : 11.5 V
		Nominal Voltage : 14.4 V
Core SWX	NANO CORE	Shutdown Voltage : 10.0 V
		Nominal Voltage : 14.8 V
Dracast	DS-90SC	Shutdown Voltage : 11.0 V
		Nominal Voltage : 14.8 V
IDX	DUO-C190	Shutdown Voltage : 11.0 V
		Nominal Voltage : 14.4 V
	DUO-C95	Shutdown Voltage : 12.0 V
		Nominal Voltage : 14.4 V
	BP-H120A	Shutdown Voltage : 10.0 V
		Nominal Voltage : 12.0 V
	BP-H110A	Shutdown Voltage : 10.0 V
		Nominal Voltage : 13.2 V
NEP	BL-BP65S	Shutdown Voltage : 10.5 V
		Nominal Voltage : 14.8 V
	Li-12	Shutdown Voltage : 10.0 V
		Nominal Voltage : 13.2 V
	NH-1200S	Shutdown Voltage : 9.0 V
		Nominal Voltage : 12.0 V
	NB-12	Shutdown Voltage : 10.0 V
		Nominal Voltage : 12.0 V
Talentcell	YB1206000	Shutdown Voltage : 10.0 V
		Nominal Voltage : 12.0 V
VariZoom	VZS8073N	Shutdown Voltage : 12.5 V
		Nominal Voltage : 14.4 V

Note:

- Operation check was done by our own standards.
We cannot be responsible for any defect or breakdown occurring during using the external power supplies listed above.
- Due to specification change, such external power supplies may not be used even with the same model numbers.
We cannot guarantee full functionality with the models listed above.